
	<b>24 Hour Emergency Telephone: 908-859-2151</b> <b>CHEMTREC: 1-800-524-6300</b>
	<b>National Response In Canada</b> <b>CANUTEC: 613-966-6666</b>
<b>From: Mallinckrodt Baker, Inc.</b> <b>222 Red School Lane</b> <b>Phillipsburg, NJ 08865</b>	
<b>Outside U.S. and Canada</b> <b>Chemtec: 703-527-3887</b>	<b>NOTE: CHEMTREC, CANUTEC and National Response Center emergency numbers to be used only in the event of chemical emergencies involving a spill, leak, fire, exposure or accident involving chemicals.</b>
<small>All non-emergency questions should be directed to Customer Service (1-800-582-2537) for assistance.</small>	

## SODIUM BISULFATE

### 1. Product Identification

**Synonyms:** Sodium hydrogen sulfate; sodium acid sulfate; sulfuric acid, monosodium salt, monohydrate  
**CAS No.:** 7681-38-1 (Anhydrous)  
**Molecular Weight:** 138.08  
**Chemical Formula:** NaHSO<sub>4</sub> · H<sub>2</sub>O  
**Product Codes:**  
 J.T. Baker: 3534  
 Mallinckrodt: 7432

### 2. Composition/Information on Ingredients

Ingredient	CAS No	Percent	Hazardous
Sodium Bisulfate	7681-38-1	90 - 100%	Yes

### 3. Hazards Identification

#### Emergency Overview

**DANGER! CORROSIVE. CAUSES BURNS TO ANY AREA OF CONTACT. MAY BE HARMFUL OR FATAL IF SWALLOWED.**

**J.T. Baker SAF-T-DATA<sup>(tm)</sup> Ratings (Provided here for your convenience)**

Health Rating: 2 - Moderate  
 Flammability Rating: 0 - None  
 Reactivity Rating: 0 - None  
 Contact Rating: 3 - Severe (Corrosive)  
 Lab Protective Equip: GOGGLES & SHIELD; LAB COAT & APRON; VENT HOOD; PROPER GLOVES  
 Storage Color Code: White (Corrosive)

#### Potential Health Effects

**Inhalation:**  
 Inhalation produces damaging effects on the mucous membranes and upper respiratory tract. Symptoms may include irritation of the nose and throat, and labored breathing. May cause lung edema, a medical emergency.

**Ingestion:**  
 Corrosive. Swallowing can cause severe burns of the mouth, throat, and stomach, leading to death. Can cause sore throat, vomiting, diarrhea.

**Skin Contact:**  
 Corrosive. Symptoms of redness, pain, and severe burn can occur.

**Eye Contact:**  
 Acidic irritant. Pain, tearing and redness can occur. Crystalline dust may also be abrasive. Solutions are acidic and splashes may cause eye damage.

**Chronic Exposure:**  
 Lung irritation, tracheal bronchitis, persistent coughing, and corrosion of teeth are possible effects from long term exposure to dust, mist or fumes from wet or moist sodium bisulfate.

**Aggravation of Pre-existing Conditions:**  
 No information found.

### 4. First Aid Measures

**Inhalation:**  
 Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.

**Ingestion:**  
 If swallowed, DO NOT INDUCE VOMITING. Give large quantities of water. Never give anything by mouth to an unconscious person. Get medical attention immediately.

**Skin Contact:**  
 Immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Get medical attention immediately. Wash clothing before reuse. Thoroughly clean shoes before reuse.

**Eye Contact:**  
 Immediately flush eyes with plenty of water for at least 15 minutes, lifting lower and upper eyelids occasionally. Get medical attention immediately.

### 5. Fire Fighting Measures

**Fire:**  
 Not considered to be a fire hazard.

**Explosion:**  
 Not considered to be an explosion hazard.

**Fire Extinguishing Media:**  
 Use any means suitable for extinguishing surrounding fire. Water may be used to cool containers and to knock down vapors in a fire situation. Do not use water on material itself or allow water to get inside container.

**Special Information:**  
 In the event of a fire, wear full protective clothing and NIOSH-approved self-contained breathing apparatus with full facepiece operated in the pressure demand or other positive pressure mode.

### 6. Accidental Release Measures

Ventilate area of leak or spill. Keep unnecessary and unprotected people away from area of spill. Wear appropriate personal protective equipment as specified in Section 8. Spills: Pick up and place in a suitable container for reclamation or disposal, using a method that does not generate dust.

### 7. Handling and Storage

Keep in a tightly closed container, stored in a cool, dry, ventilated area. Protect against physical damage. Isolate from incompatible substances. Containers of this material may be hazardous when empty since they retain product residues (dust, solids); observe all warnings and precautions listed for the product.

### 8. Exposure Controls/Personal Protection

**Airborne Exposure Limits:**  
 None established.

**Ventilation System:**  
 A system of local and/or general exhaust is recommended to keep employee exposures as low as possible. Local exhaust ventilation is generally preferred because it can control the emissions of the contaminant at its source, preventing dispersion of it into the general work area. Please refer to the ACGIH document, *Industrial Ventilation, A Manual of Recommended Practices*, most recent edition, for details.

**Personal Respirators (NIOSH Approved):**  
 If the exposure limit is exceeded and engineering controls are not feasible, a half-face respirator with an acid gas cartridge and particulate (NIOSH type N95 or better) filter may be worn for up to ten times the exposure limit or the maximum use concentration specified by the appropriate regulatory agency or respirator supplier, whichever is lowest. A full-face piece respirator with an acid gas cartridge and particulate (NIOSH type N100) filter may be worn up to 50 times the exposure limit, or the maximum use concentration specified by the appropriate regulatory agency, or respirator supplier, whichever is lowest. If oil particles (e.g. lubricants, cutting fluids, glycerine, etc.) are present, use a NIOSH type R or P filter. For emergencies or instances where the exposure levels are not known, use a full-facepiece positive-pressure, air-supplied respirator. WARNING: Air-purifying respirators do not protect workers in oxygen-deficient atmospheres.

**Skin Protection:**  
 Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact.

**Eye Protection:**  
 Use chemical safety goggles and/or full face shield where dusting or splashing of solutions is possible. Maintain eye wash fountain and quick-drench facilities in work area.

### 9. Physical and Chemical Properties

**Appearance:**  
 Colorless crystals.

**Odor:**  
 Odorless.

**Solubility:**  
 67g/100g water.

**Density:**  
 2.10

**pH:**  
 1.4

**% Volatiles by volume @ 21C (70F):**  
 0

**Boiling Point:**  
 Not applicable.

**Melting Point:**  
 58C (136F)

**Vapor Density (Air=1):**  
 No information found.

**Vapor Pressure (mm Hg):**  
 No information found.

**Evaporation Rate (BuAc=1):**  
 No information found.

### 10. Stability and Reactivity

**Stability:**  
 Stable under ordinary conditions of use and storage. Hygroscopic.

**Hazardous Decomposition Products:**  
 Oxides of sulfur and the contained metal.

**Hazardous Polymerization:**  
 Will not occur.

**Incompatibilities:**  
 Strong bases, calcium hypochlorite and sodium carbonate.

**Conditions to Avoid:**  
 Moisture, dusting and incompatibles.

### 11. Toxicological Information

No LD50/LC50 information found relating to normal routes of occupational exposure. Anhydrous salt has been investigated as a mutagen.

Ingredient	--NTP Carcinogen--	Anticipated	IARC Category
Sodium Bisulfate (7681-38-1)	No	No	None

### 12. Ecological Information

**Environmental Fate:**  
 No information found.

**Environmental Toxicity:**  
 No information found.

### 13. Disposal Considerations

Whatever cannot be saved for recovery or recycling should be managed in an appropriate and approved waste facility. Although not a listed RCRA hazardous waste, this material may exhibit one or more characteristics of a hazardous waste and require appropriate analysis to determine specific disposal requirements. Processing, use or contamination of this product may change the waste management options. State and local disposal regulations may differ from federal disposal regulations. Dispose of container and unused contents in accordance with federal, state and local requirements.

### 14. Transport Information

**Domestic (Land, D.O.T.)**

**Proper Shipping Name:** CORROSIVE SOLID, ACIDIC, INORGANIC, N.O.S. (SODIUM BISULFATE)

**Hazard Class:** 8

**UN/NA:** UN3260

**Packing Group:** III

**Information reported for product/size:** 12KG

**International (Water, I.M.O.)**

**Proper Shipping Name:** CORROSIVE SOLID, ACIDIC, INORGANIC, N.O.S. (SODIUM BISULFATE)

**Hazard Class:** 8

**UN/NA:** UN3260

**Packing Group:** III

**Information reported for product/size:** 12KG

**International (Air, I.C.A.O.)**

**Proper Shipping Name:** CORROSIVE SOLID, ACIDIC, INORGANIC, N.O.S. (SODIUM BISULFATE)

**Hazard Class:** 8

**UN/NA:** UN3260

**Packing Group:** III

**Information reported for product/size:** 12KG

### 15. Regulatory Information

Ingredient	TSCA	EC	Japan	Australia
Sodium Bisulfate (7681-38-1)	Yes	Yes	Yes	Yes

Ingredient	Korea	--Canada--	DSL	NDSL	Phil.
Sodium Bisulfate (7681-38-1)	Yes	Yes	No	Yes	

Ingredient	RQ	TPQ	List	Chemical Catg.
Sodium Bisulfate (7681-38-1)	No	No	No	No

Ingredient	CERCLA	RCRA	TSCA
Sodium Bisulfate (7681-38-1)	No	No	8(d)

Chemical Weapons Convention: No TSCA 12(b): No CDTA: No  
 SARA 311/312: Acute: Yes Chronic: Yes Fire: No Pressure: No  
 Reactivity: No (Mixture / Solid)

**Australian Hazchem Code:** 2X

**Poison Schedule:** S5

**WHMIS:**  
 This MSDS has been prepared according to the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all of the information required by the CPR.

### 16. Other Information

**NFPA Ratings:** Health: 3 Flammability: 0 Reactivity: 0

**Label Hazard Warning:**  
 DANGER! CORROSIVE. CAUSES BURNS TO ANY AREA OF CONTACT. MAY BE HARMFUL OR FATAL IF SWALLOWED.

**Label Precautions:**  
 Do not get in eyes, on skin, or on clothing.  
 Do not breathe dust.  
 Keep container closed.  
 Use only with adequate ventilation.  
 Wash thoroughly after handling.

**Label First Aid:**  
 In case of contact, immediately flush eyes or skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash clothing before reuse. If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. If swallowed, DO NOT INDUCE VOMITING. Give large quantities of water. Never give anything by mouth to an unconscious person. In all cases get medical attention immediately.

**Product Use:**  
 Laboratory Reagent.

**Revision Information:**  
 MSDS Section(s) changed since last revision of document include: 14.

**Disclaimer:**  
 \*\*\*\*\*

Mallinckrodt Baker, Inc. provides the information contained herein in good faith but makes no representation as to its comprehensiveness or accuracy. This document is intended only as a guide to the appropriate precautionary handling of the material by a properly trained person using this product. Individuals receiving the information must exercise their independent judgment in determining its appropriateness for a particular purpose.

MALLINCKRODT BAKER, INC. MAKES NO REPRESENTATIONS OR WARRANTIES, EITHER EXPRESS OR IMPLIED, INCLUDING WITHOUT LIMITATION ANY WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE WITH RESPECT TO THE INFORMATION SET FORTH HEREIN OR THE PRODUCT TO WHICH THE INFORMATION REFERS. ACCORDINGLY, MALLINCKRODT BAKER, INC. WILL NOT BE RESPONSIBLE FOR DAMAGES RESULTING FROM USE OF OR RELIANCE UPON THIS INFORMATION.

\*\*\*\*\*

**Prepared by:** Environmental Health & Safety

**Phone Number:** (314) 654-1600 (U.S.A.)